

SPECIFICATIONS

U.S. Measurements

| | Power Required | Pressure | Max. Speed | Max. Flow | Max. Temp. | Plunger ø | Plunger Stroke | Weight | NPSHR |
|--------|----------------|----------|------------|-----------|------------|-----------|----------------|--------|-------------|
| Model | BHP | PSI | RPM | GPM | °F | in | in | lbs. | ft. of head |
| GP6128 | 51.4 | 4350 | 800 | 18.0 | 140 | 1.10 | 1.89 | 309 | 23.6 |

Metric Measurements

| | Power Required | Pressure | Max. Speed | Max. Flow | Max. Temp. | Plunger ø | Plunger Stroke | Weight | NPSHR |
|--------|----------------|----------|------------|-----------|------------|-----------|----------------|--------|-------|
| Model | kW | bar | RPM | l/min | °C | mm | mm | kg | mWs |
| GP6128 | 38.3 | 300 | 800 | 68.1 | 60 | 28 | 48 | 140 | 7.2 |

INSTALLATION INSTRUCTIONS

Performance data for intermittent operation, data for continuous operation on request.

For information on intermittent operation and calculating of the performance data, see the Giant Industries assembly instructions.

NPSHR / Inlet pressure

Required NPSH refers to water (at 68 °F [20°C]) at maximum permissible pump speed.

The inlet pressure on the suction side must not exceed 29 PSI (2 bar).

Make sure that suction pulsation is sufficiently dampened – water column resonance must be avoided.

Level of noise emission

Emission sound pressure level: ≤ 92 dB(A)

Fields of application

The fields of application of these pump types correspond to the specifications in the assembly instructions Giant Industries.

Ambient conditions

Ambient temperature: $41\text{ °F} < T_{\text{Amb.}} < 86\text{ °F}$

Ambient temperature: $5\text{ °C} < T_{\text{Amb.}} < 30\text{ °C}$

Oil filling

- Filling quantity: **1.1 gal (4.2 l)**
- Quality: Industrial gear oil **ISO VG 220** or automotive gear oil **SAE 90 GL4 (Giant's p/n 01154)**
- Intervals: first oil change after **50 operating hours**, then every **1000 operating hours**, but at the latest after **12 months**.

Installation/ Putting into Operation

Shaft protector

When the pump is in operation, the open shaft end must be covered up by shaft protector (21), the driven shaft side and coupling by a contact-protector and the plunger room by cover (30).

Direction of pump rotation

Set the direction of rotation of the drive unit according to the direction of rotation arrow on the crankcase.

Suction line filter

Recommended mesh size 150 µm.

Operation

For informations, see assembly instructions Giant Industries, Inc.