



Flat Jet Insert Nozzles Form C

Z41-2e



For use with spraying equipment and water tools up to an operating pressure of 21,750 PSI (1500 bar)

Technical Data

- Working Pressure: 21,750 PSI (1500 bar)
- Sealing by means of o-ring
- Material: Stainless Steel 1.4034 hardened
- Nozzle factor: 0.67
- Nozzle factor: 0.95

ø (mm)	Max. p PSI (bar)	Part No.			
		10°	15°	20°	30°
0.80	21,750 (1500)	7005543	7001212	7005577	7001235
0.90		7005544	7001213	7005578	7001236
1.00		7005545	7001214	7005579	7001237
1.10		7005546	7001215	7005580	7001238
1.20		7005547	7001216	7005581	7001239
1.30		7005548	7001217	7005582	7001240
1.40		7005549	7001218	7005583	7001241
1.50		7005550	7001219	7005584	7001242
1.60		xxx	7001220	xxx	7001243
1.70		xxx	7001221	xxx	7001244
1.80		xxx	7001222	xxx	7001245
1.90		xxx	7001223	xxx	7001246
2.00		xxx	7001224	xxx	7001247
2.10		xxx	7001225	xxx	7001248
2.20		xxx	7001226	xxx	7001249
2.30		xxx	7001227	xxx	7001250
2.40		xxx	7001228	xxx	7001251
2.50		xxx	7001229	xxx	7001252
2.60		xxx	7001230	xxx	7001253
2.70		xxx	7001231	xxx	7001254
2.80	xxx	7001232	xxx	7001255	
O-Ring		1060382			