

HPUDT-10-10 Series



10 GPM @ 10,000 PSI*

*other flows and pressures available

Ruggedly designed pump and diesel unit which features a compact design and continuous duty pump and over-sized engine. Available in a standard design or let us create a customized unit to meet your needs.

Applications:

- Surface Preparation
- Paint Removal
- Deburring

- Tank Cleaning
- · Hydrostatic Testing
- Heat Exchanger Cleaning

Standard Version:

- 110 HP Diesel engine, turbo charged with over-center clutch
- High pressure pump with spheroidal cast iron crankcase, drop-forged hardened, ground and polished crankshaft, bronze connecting rods and hardened stainless steel plungers
- Flow (soft) unloader (rated to 15,000 PSI)
- Safety Valve (rated for 15,000 PSI) which is adjustable and is capable of working mulitple times
- · Heavy duty trailer, rated for 14,000 lb. load
- Water supply tank (200 gallons)
- Boost pump
- Diesel fuel supply of 35 gallons
- · Manual adjustment of engine speed
- Gun/wand/nozzle/hose assembly
- Tool Box
- 12 volt battery for electric start
- Inlet "Y" strainer
- All necessary plumbing
- Manual
- Gross weight: 5880 lbs.

Optional Equipment:

- · Electronic controls for speed control of engine
- Hydrostatic test unit including bleed-off control
- · Automatic water fill valve
- · Low water shut down
- Skid mounted versions
- Heavy duty filter with low inlet pressure alarm and connections

