

	Pump	LH/RH	DRIVE	SHAFT	BACKEND	UNLOADER	INJECTOR SIZE	THERMAL	OIL
Pump Model	P205	0.38 GPM @ 2000 PSI @ 1750 RPM and 0.8 GPM @ 2500 PSI @ 3450 RPM							
	P206	0.74 GPM @ 2000 PSI @ 1750 RPM and 1.5 GPM @ 2500 PSI @ 3450 RPM							
	P207	0.9 GPM @ 2000 PSI @ 1750 RPM and 1.7 GPM @ 2000 PSI @ 3450 RPM							
	P225	0.9 GPM @ 2000 PSI @ 1750 RPM and 1.8 GPM @ 2000 PSI @ 3450 RPM							
	P208	1.0 GPM @ 2000 PSI @ 1750 RPM and 1.9 GPM @ 2500 PSI @ 3450 RPM							
	P230	1.1 GPM @ 2500 PSI @ 1750 RPM and 2.0 GPM @ 2500 PSI @ 3450 RPM							
	P209	1.5 GPM @ 2000 PSI @ 1750 RPM and 2.7 GPM @ 2500 PSI @ 3450 RPM							
	P226	1.5 GPM @ 2000 PSI @ 1750 RPM							
	P223	1.7 GPM @ 2000 PSI @ 1750 RPM and 3.0 GPM @ 3000 PSI @ 3450 RPM							
	P210	1.8 GPM @ 2000 PSI @ 1750 RPM and 3.3 GPM @ 2000 PSI @ 3450 RPM							
	P217	1.8 GPM @ 2000 PSI @ 1750 RPM and 3.3 GPM @ 2500 PSI @ 3450 RPM							
	P228	1.8 GPM @ 3000 PSI @ 1750 RPM							
	P211	2.1 GPM @ 2000 PSI @ 1750 RPM and 3.8 GPM @ 2000 PSI @ 3450 RPM							
	P227	2.1 GPM @ 2500 PSI @ 1750 RPM							
	P221	2.3 GPM @ 2000 PSI @ 1750 RPM and 4.2 GPM @ 2500 PSI @ 3450 RPM							
	P218	3.4 GPM @ 2500 PSI @ 1750 RPM							
P219	4.2 GPM @ 2500 PSI @ 1750 RPM								
P220	4.7 GPM @ 2500 PSI @ 1450 RPM								
Shaft Side	LH Shaft	L							
	RH Shaft	R							
Electric Motor	(56C) 5 7/8" or 5.11" dia.	E1	(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435)						
	(TC Face) 7 1/4" dia. Bolts	E2	(1) 06495 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07803)						
Gas Motor	(Under 9HP) 3-5/8" dia. Bolts	G1	(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435 & (1) 09103)						
	(9HP & More) 6.5" dia. Bolts	G2	(1) 06478 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07804 & (4) 13129						
	(9HP & More) 6.5" dia. Bolts	B1	(1) 08499A				& (4) 13445 if needed		
	(16HP & More) 6.5" dia. Bolts	B2	(1) 08980 or (1) 08981						
Coupler Size	5/8" Aluminum = 06505-0.6	B	(1) 06299 AND (1) 06332 with Each Aluminum Coupler ***** (1) 06332 with each plastic coupler						
	5/8" Delrin = 08494P	I							
	3/4" Aluminum = 06505-0.7	C							
	3/4" Delrin = 08496P	J							
	7/8" Aluminum = 06505-0.8	D							
	24mm Aluminum = 06505-24	M							
	1" Aluminum = 06505-1.0	E							
	1" Delrin = 08485P	K							
	1 1/8" Aluminum = 06505-1.1	F							
	1 1/8" Delrin = 08487P	L							
	1 3/8" Aluminum = 04393-1.3	H							
1 3/8" Delrin = 08489P	N								
Backend	Extended 08302-L(P200)						(4) 01196 / (4) 01176-2		
	Short Backend 08302(P200)	X					(4) 07188 / (4) 01176-2		
Unloader/Regulator	No Unloader/Regulator	\							
	Unloader/Regulator	23270 (P200)					U or R	For Regulators, add "R"	
	Unloader (Side of Shaft)	23270 (P200)					US or RS	For Regulators, add "R"	
Siphon Injector	1.8mm (Fixed)						23750-1.8	2	
	2.1mm (Fixed)						23750-2.1	3	
	2.3mm (Fixed)						23750-2.3	4	
	1.8mm (Adjustable)						23750-1.8A	6	
	2.1mm (Adjustable)						23750-2.1A	7	
	2.3mm (Adjustable)						23750-2.3A	8	
Thermal	Thermal (Blank if No Thermal Relief Valve)						23422B (1/2")	T	
Oil	7.5 ounces for short gear ends / 9.0 ounces for long gear ends							O	
NOTE: Pumps without Bell Housing to include (1) 01067 Associated parts									
Method: Follow "shaded" boxes to follow the part number. Corresponding items included, next to the box.									