

	Pump	LH/RH	DRIVE	SHAFT	BACKEND	UNLOADER	INJECTOR SIZE	THERMAL	OIL
Pump Model	P327	2.9 GPM @ 3500 PSI (4000 PSI*) @ 3450 RPM							
	P317	3.5 GPM @ 3045 PSI (3350 PSI*) @ 1750 RPM							
	P323	3.5 GPM @ 3685 PSI @ 1750 RPM							
	P340	3.7 GPM @ 3500 PSI (4000 PSI*) @ 1750 RPM							
	P321	3.8 GPM @ 3200 PSI (3500 PSI*) @ 3450 RPM							
	P314	3.8 GPM @ 3500 PSI (4000 PSI*) @ 3450 RPM							
	P316	4.0 GPM @ 3045 PSI (3350 PSI*) @ 1450 RPM and 4.7 GPM @ 2500 PSI (2750 PSI*) @ 1750 RPM							
	P322	4.0 GPM @ 3500 PSI @ 1450 RPM and 4.7 GPM @ 3000 PSI @ 1750 RPM							
	P328	4.1 GPM @ 3200 PSI (3500 PSI*) @ 3450 RPM							
	P329	4.1 GPM @ 3500 PSI (4000 PSI*) @ 3450 RPM							
	P318	4.8 GPM @ 2000 PSI @ 1450 RPM and 5.8 GPM @ 1000 PSI @ 1750 RPM							
	P324	4.8 GPM @ 2200 PSI @ 1450 RPM and 5.8 GPM @ 1100 PSI @ 1750 RPM							
	P319	4.8 GPM @ 2500 PSI (2750 PSI*) @ 3450RPM							
	P332	4.8 GPM @ 3000 PSI @ 1450 RPM							
	P325	4.8 GPM @ 3045 PSI @ 3450 RPM							
P334	5.5 GPM @ 2000 PSI @ 1450 RPM								
P330	6.5 GPM @ 1000 PSI @ 3450 RPM								
Shaft Side	LH Shaft	L							
	RH Shaft	R		*Intermittent duty					
Electric Motor	(56C) 5 7/8" or 5.11" dia.	E1		(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435)					
	(TC Face) 7 1/4" dia. Bolts	E2		(1) 06495 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07803)					
Gas Motor	(Under 9HP) 3-5/8" dia. Bolts	G1		(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435 & (1) 09103)					
	(9HP & More) 6.5" dia. Bolts	G2		(1) 06478 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07804 & (4) 13129					
	(9HP & More) 6.5" dia. Bolts	B1		(1) 08499A				& (4) 13445 if needed	
	(16HP & More) 6.5" dia. Bolts	B2		(1) 08980 or (1) 08981					
Coupler Size	5/8" Aluminum = 06505-0.6	B		(1) 06299 AND (1) 06332 with Each Aluminum Coupler ***** (1) 06332 with each plastic coupler					
	5/8" Delrin = 08494P	I							
	3/4" Aluminum = 06505-0.7	C							
	3/4" Delrin = 08496P	J							
	7/8" Aluminum = 06505-0.8	D							
	24mm Aluminum = 06505-24	M							
	1" Aluminum = 06505-1.0	E							
	1" Delrin = 08485P	K							
	1 1/8" Aluminum = 06505-1.1	F							
	1 1/8" Delrin = 08487P	L							
	1 3/8" Aluminum = 04393-1.3	H							
1 3/8" Delrin = 08489P	N								
Backend	Extended 08410-LG (P300)					(4) 01196 / (4) 01176-2			
	Short Backend 08410B (P300)	X				(4) 07188 / (4) 01176-2			
Unloader/Regulator	No Unloader/Regulator	\							
	Unloader/Regulator	23280 (P300)				U or R		For Regulators, add "R"	
	Unloader (Side of Shaft)	23280 (P300)				US or RS		For Regulators, add "R"	
Siphon Injector	1.8mm (Fixed)					23750-1.8		2	
	2.1mm (Fixed)					23750-2.1		3	
	2.3mm (Fixed)					23750-2.3		4	
	1.8mm (Adjustable)					23750-1.8A		6	
	2.1mm (Adjustable)					23750-2.1A		7	
	2.3mm (Adjustable)					23750-2.3A		8	
Thermal	Thermal (Blank if No Thermal and Pulsator Valve)					23422B (1/2")		T	
Pulsator	Pulsator (Blank if No Pulsator Valve)					P			
NOTE: Pumps without Bell Housing to include (1) 01067 Associated parts									
Method: Follow "shaded" boxes to follow the part number. Corresponding items included, next to the box.									